

# Stabic®



## SPECIFICATION

### TWO RELAY CONTROL

MODEL	INPUT	OUT PUT
ST-1000	160V - 240V	220V ± 8%
ST-1200	160V - 240V	220V ± 8%
ST-1600	160V - 240V	220V ± 8%
ST-2250	160V - 240V	220V ± 8%
ST-4000	160V - 240V	220V ± 8%
ST-5000	160V - 240V	220V ± 8%
ST-7000	160V - 240V	220V ± 8%

### THREE RELAY CONTROL

MODEL	INPUT	OUT PUT
ST-1200/3R	135V - 240V	220V ± 8%
ST-1600/3R	135V - 240V	220V ± 8%

### TIME DELAY FEATURE

MODEL	INPUT	OUT PUT
ST-1200-TD	160V - 240V	220V ± 8%
ST-1600-TD	160V - 240V	220V ± 8%
ST-2250-TD	160V - 240V	220V ± 8%

### OVER VOLTAGE CONTROL

MODEL	INPUT	OUT PUT
ST-1200/OV	160V - 260V	220V ± 8%
ST-1600/OV	160V - 260V	220V ± 8%

Distributed by: Mohsin Yunus Electronics  
 9, Elahi Centre, Saddar, Regal, Karachi 74400 Pakistan  
 Ph: 021-2768674 021- 2723340 Fax: 021- 2768684  
 E mail mohsin.yunus@cyber.net.pk